



An die interessierte Partei / To whom it may concern

Dr. Stefan Dreiheller
Quality Unit / Regulatory Affairs

Date of issue: 12.12.2019
Page 1/2
Doc.-No. EIP-1035-C
Revision 4

Elemental impurities

Ph. Eur. General Text 5.20; USP-NF General Chapter <232> and <233>; ICH Guideline Q3D

Meggle products:

- Anhydrous Lactose USP-NF / Ph. Eur. / JP: DuraLac® H

In the production process of the above mentioned products, the elements classified in Class 1, 2A, 2B and 3 are not intentionally added in form of metal catalysts, metal reagents etc.

Permitted concentrations limits were calculated using the Permitted Daily Exposures and assuming a daily intake of the excipients of 10 g (ICH Q3D, No 7 Option 1, stated in table A.2.2). Acceptance levels were defined as 30% of the permitted concentrations.

Testing was conducted for the elements categorised as Class 1, 2A and 3 relevant for oral route of administration according to the ICH Guideline Q3D. Several representative lots of the products were tested using ICP-MS method in conformance to USP-NF <233>. Testing method has been validated for the matrix of the products.

Representative results are shown for the product on the table below. All results are far below 30% of the acceptance levels for oral application. In consequence, additional controls are not required.

MEGGLE has implemented an ongoing monitoring program for elemental impurities in accordance to the regime of the initial study performed.

Freundliche Grüße / Best regards

Molkerei MEGGLE Wasserburg GmbH & Co. KG


Dr. Stefan Dreiheller



Elemental impurities – Summary Results

Ph. Eur. General Text 5.20; USP-NF General Chapter <232> and <233>; ICH Guideline Q3D

Material Name Anhydrous Lactose
 Manufacturer Agropur inc., 719 North Main Street, Le Sueur, MN 56058-1404, USA
 Source/Type of Excipient Animal derived (Milk of bovine origin).
 Route of administration (RoA) Oral

Date of issue: 12.12.2019
 Page 2/2
 Doc.-No. EIP-1035-C
 Revision 4

Class	Elements	Elements to be considered		Oral PDE µg/day	Perm. Conc. µg/g	Accept. Level µg/g	Representative Results * DuraLac® H µg/g	Method	Comments	
		Added	Based on RoA							
1	Cadmium	Cd	No	Yes	5	0.5	0.15	< 0.0009	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
1	Lead	Pb	No	Yes	5	0.5	0.15	< 0.0006	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
1	Arsenic (inorg.)	As	No	Yes	15	1.5	0.45	< 0.0081	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
1	Mercury (inorg.)	Hg	No	Yes	30	3	0.9	< 0.0005	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
2A	Cobalt	Co	No	Yes	50	5	1.5	0.0003	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
2A	Vanadium	V	No	Yes	100	10	3	< 0.0093	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
2A	Nickel	Ni	No	Yes	200	20	6	< 0.0084	ICP-MS; USP 40 NF35 <233>	3 batches tested. Monitoring installed (1 / year)
2B	Thallium	Tl	No	No	n/a					
2B	Gold	Au	No	No	n/a					
2B	Palladium	Pd	No	No	n/a					
2B	Iridium	Ir	No	No	n/a					
2B	Osmium	Os	No	No	n/a					
2B	Rhodium	Rh	No	No	n/a					
2B	Ruthenium	Ru	No	No	n/a					
2A	Selenium	Se	No	No	n/a					
2B	Silver	Ag	No	No	n/a					
2B	Platinum	Pt	No	No	n/a					
3	Lithium	Li	No	No	n/a					
3	Antimony	Sb	No	No	n/a					
3	Barium	Ba	No	No	n/a					
3	Molybdenum	Mo	No	No	n/a					
3	Copper	Cu	No	No	n/a					
3	Tin	Sn	No	No	n/a					
3	Chromium	Cr	No	No	n/a					

* "< X" implies values are below LoQ (limit of quantification) which is X

Molkerei MEGGLE Wasserburg GmbH & Co. KG • Megglestr. 6-12 • 83512 Wasserburg am Inn
 Telefon +49 (0) 8071 73-0 • Fax +49 (0) 8071 73-444 • info@meggle.de • www.meggle.com

Rechtsform Kommanditgesellschaft • Sitz Wasserburg am Inn • Registergericht AG Traunstein HRA 7828 • persönlich haftende Gesellschafterin:

MEGGLE Wasserburg Verwaltungs GmbH • Sitz Wasserburg am Inn • Registergericht AG Traunstein HRB 14178

Geschäftsführer: Matthias Oettel (Vorsitzender) • Marcus Hornmuth • Dr. Franz Mayer

Ust.-IdNr.: DE813497582 • St-Nr. 156/116/00116